

## **A BARRAGE OF LOW INTENSITY ZOOM-PPM**

ZOM-MRP - Obstruction lights low intensity led

**ZOM-MRP - saving led obstruction lights low intensity lamp for light marking of high-altitude and extended objects bridges, tall buildings and radio towers teletranslation antenna-feeder devices, cellular operators, airports, airfields, heliports helipads on buildings, etc. in a housing of impact resistant polycarbonate ZOOM-PMA ZOM-ZOM PMB-PPMV.**

**ZOM-MRP-But with the power of light is 10 CD the Candela and built-in housing light source - one Board of LEDs**

**ZOM-PPM-B with an intensity equal to 20 CD the Candela and built-in housing light source - two led boards**

**ZOM-MRP-In with the power of light is equal to 32 KD Candela and built-in housing light source - three Board LEDs.**

**The main advantages of lights ZOM-MRP are durability up to 100,000 hours or nearly 12 years of continuous operation energy-saving environmental safety, and so on. All products are made**

**red - K**

**yellow - W**

**green - L**

**blue -**

**white - B color but can be manufactured with a different color.**

**Obstacle lights are made in housings of impact resistant polycarbonate with colored or transparent flasks with different characteristics on light intensity. These products come with built-in light source based on LEDs.**

**Led lighting device-type ZOOM is a barrage of low intensity. In this unit used a specially designed LEDs that allows to obtain an optimal radiation diagram and luminous intensity corresponding to the requirements of the MAC AP-170 CRAIG of the Russian Federation and ICAO as well as high reliability of the product.**

**The device is intended for light marking of high-altitude and extended objects pose a threat to air traffic safety and for permanent glow on the ground objects as a signal light.**

**Operating temperature range from - 60 to + 60 With**

**Climatic version UHL1**

**The filter is colourless transparent**

Link to article:: [A BARRAGE OF LOW INTENSITY ZOOM-PPM](#)