

Led floodlights

G. Mosqueteros shosse 157 page 9 In the basket 0 units in the amount of 0 RUB Light source type led Viewing angle 140 ° Luminous flux 4250 - 4500 Lm Degree of protection IP65 Color temperature from 3000-6000K Working voltage 100-265 V Service life 50 000 hours Light source type led Viewing angle 140 ° Luminous flux 9000-9500lm Degree of protection IP65 Color temperature from 3000-6000K Working voltage 100-265 V Service life 50 000 hours Light source type led Viewing angle 140 ° Luminous flux 12500-13000lm Degree of protection IP65 Color temperature from 3000-6000K Working voltage 100-265 V Service life 50 000 hours Looking for equipment for industrial and street lighting please Contact LEDERLE. We are engaged in manufacturing of led lighting lamps and spotlights. These devices will allow to create necessary conditions and to save much money. Fixture can be purchased retail or wholesale. The larger the batch the lower the cost of production. Led flood lights LD equipped with highly efficient lighting units. They are guaranteed to last without breakdowns for over 30,000 hours approximately 35 years of continuous work. The range includes devices with different characteristics. You can choose the led spotlight which will be optimal for a particular object in brightness and temperature the luminous flux. We supply the fixture with warm cool and multi-colored radiation. Features of led floodlights Products of our online store are of high quality at optimum cost. It is possible to allocate following advantages of buying projectors in LEDERLE To consult with a specialist about the equipment of the terms of payment and delivery please call on the website. Fill in the form and our specialist will contact you within 20 minutes. The asterisk indicates fields are required

Link to article:: [Led floodlights](#)